


[Web](#) [Images](#) [Video](#) [News](#) [Maps](#) [more »](#)


[Advanced Scholar Search](#)  
[Scholar Preferences](#)  
[Scholar Help](#)
[Scholar](#)   [All articles](#) - [Recent articles](#)

Results 1 - 10 of about 45 for "bucket array" pointer counter. (0.11 seconds)

[FS] [The reactive tabu search](#) - all 5 versions »

R Battiti, G Techioni - *CIRSA Journal on Computing*, 1994 - [rim.science.univr.it](#)

... time := current.time pointer \* repetitions := pointer \* repetitions + 1 if pointer \* repetitions > Rep ... 1 if chaotic > Chaos then begin Reset counter and execute ...

Cited by 496 - [Related Articles](#) - [View as HTML](#) - [Web Search](#) - [BL Direct](#)

[Split-ordered lists: Lock-free extensible hash tables](#) - all 5 versions »

O Shalev, N Shavit - *Journal of the ACM (JACM)*, 2006 - [portal.acm.org](#)

... points to segments of buckets, each of which is a bucket array. ... counter is initially 0, and the buckets are set as ... a node of key 0, whose next pointer is set ...

Cited by 22 - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

[Two-handed emulation: how to build non-blocking implementations of complex data-structures using ...](#) - all 3 versions »

M Greenwald - *Proceedings of the twenty-first annual symposium on ...*, 2002 - [portal.acm.org](#)

... to shared memory simultaneously increments a "program counter" (atomically ... 6), then setting the prey pointer of the ... to decide when to shrink the bucket array. ...

Cited by 22 - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

[FS] [Partially persistent dynamic sets for history-sensitive heuristics](#) - all 2 versions »

R Battiti - *Data Structures, Near Neighbor Searches, and Methodology* ... - 2002 - [rim.science.univr.it](#)

... If T changes with the iteration counter t depending on the search status, the general dynamical system that generates the search trajectory comprises an ...

Cited by 1 - [Related Articles](#) - [View as HTML](#) - [Web Search](#)

[Partially persistent dynamic sets for history-sensitive](#)

R Battiti - *Data Structures, Near Neighbor Searches, and Methodology* ... - 2002 - [books.google.com](#)

... in the appropriate bucket with a pointer time t is updated and the repetition counter is incremented ... and assuming that the bucket array size is equal to ...

[Related Articles](#) - [Web Search](#)

[Faster min-cut computation in unweighted hypergraphs/circuit netlists](#)

WK Mak - *VLSI Design, Automation and Test, 2005 (VLSI-TSA-DAT)*, 2005 ... - 2005 - [ieeexplore.ieee.org](#)

... partition of a hypergraph[4]. There is a bucket array ... e is added to subset A.

maxic - node pointers Figure 5 ... When the value of a counter becomes 1, we scan ...

[Related Articles](#) - [Web Search](#)

[FOF] [Split-ordered lists—lock-free resizable hash tables](#)

O Shalev, N Shavit - *Proceedings of the 22nd Annual ACM Symposium on Principles ...*, 2003 - [cs.tau.ac.il](#)

... points to segments of buckets, each of which is a bucket array. ... The counter is initially 0, and the buckets are set ... a node of key 0, whose next pointer is set ...

Cited by 2 - [Related Articles](#) - [View as HTML](#) - [Web Search](#) - [BL Direct](#)

[Optimal lightweight construction of suffix arrays for constant alphabets](#)

G Nong, S Zhang - *Proc. Workshop on Algorithms And Data Structures (WADS)* - Springer

... with 2 strings of T satisfying  $PS_3 = 2$ , i.e.  $P_1[i]$  gives the pointers to all ... using bucket sorting with U as the counter array and V as the bucket array. ...

Cited by 1 - [Related Articles](#) - [Web Search](#) - [BL Direct](#)

[Method and apparatus for lock-free, non-blocking hash table](#) - all 3 versions »

AV Kadatch - *US Patent 6,936,180*, 2006 - [Google Patents](#)

... the invention, the reference counter includes a node state that provides a connection between the semantically independent reference counter and pointer to the ...

[Related Articles](#) - [Web Search](#)

[FS] [Radix Sorting & Searching](#) - all 5 versions »

S Nilsson - *cs.luc.se*

... the machine: n cannot be larger than 2 w. This is a very reasonable assumption, since otherwise a pointer is too large to fit in a machine word. ...

Cited by 32 - [Related Articles](#) - [View as HTML](#) - [Web Search](#)